Extensive Journal of Applied Sciences
https://ejasj.com/index.php/EJASJ/index (Vol 2 No 1 2026)

Multiscale Computation and Intelligent Prediction for Materials Structure Design

Noah Foster
Department of Mechanical Engineering, University of Michigan, Ann Arbor, MI, USA

ABSTRACT: The discovery and optimization of advanced materials are foundational to technological progress across multiple disciplines ranging from aerospace engineering to sustainable energy production. Historically, materials design has relied upon empirical trial-and-error methodologies that are both time-consuming and resource-intensive. The contemporary paradigm has shifted toward computational design, yet traditional physics-based models remain constrained by the inherent trade-offs between accuracy and computational cost across varying spatial and temporal scales. This paper presents a comprehensive examination of the integration of multiscale computational frameworks with intelligent predictive models driven by artificial intelligence and machine learning. By bridging quantum mechanical calculations at the atomistic level, molecular dynamics at the nanoscale, phase-field modeling at the mesoscale, and finite element analysis at the macroscale, a holistic representation of material behavior is achieved. We explore the methodological architectures required to couple these disparate scales sequentially and concurrently. Furthermore, we detail the implementation of graph neural networks and active learning paradigms to serve as highly accurate surrogate models that accelerate the exploration of vast compositional and structural design spaces. The results indicate that this synthesized approach drastically reduces the computational overhead typically associated with high-fidelity simulations while maintaining predictive reliability. Ultimately, this research underscores the transformative potential of combining rigorous multiscale physics with advanced intelligent prediction to usher in a new era of accelerated materials structure design.

Keywords: Multiscale Modeling, Machine Learning, Materials Design, Predictive Computation

1. INTRODUCTION

1.1 The Imperative for Advanced Materials Design

The progress of human civilization has been inextricably linked to the mastery of materials, transitioning through historical epochs defined by the utilization of stone, bronze, iron, and eventually complex synthetic polymers and semiconductors. In the modern era, the demand for novel materials with tailored properties is driven by the urgent needs of advanced technological applications. The aerospace industry requires structural alloys that possess an unprecedented combination of high strength, low density, and extreme thermal resistance to improve fuel efficiency and enable deeper space exploration. Similarly, the transition to renewable energy systems relies heavily on the development of highly efficient photovoltaic materials, robust battery architectures with high energy densities, and advanced catalysts for hydrogen fuel production. Traditionally, the discovery of such materials has been heavily dependent upon empirical trial-and-error laboratory experiments [1]. This Edison-style approach involves synthesizing numerous variations of a material, subjecting them to rigorous physical testing, and iteratively refining the composition based on observed outcomes. While historically successful, this methodology is fundamentally limited by its linear nature, high financial costs, and the sheer length of time required to bring a new material from conceptualization to commercial deployment, a process that historically

averages two decades. The vastness of the chemical space further exacerbates this challenge. The number of possible stable compounds that can be formed from the periodic table is astronomically large, rendering an exhaustive experimental search practically impossible. Consequently, there is an urgent and critical imperative to transition away from empirical serendipity toward rational, predictive, and deliberate materials design paradigms [2]. This transition forms the core motivation for the integration of advanced computational techniques into the field of materials science.

1.2 Evolution of Computational Approaches

The advent of computational materials science marked a significant paradigm shift, offering the potential to simulate material properties in silico before physical synthesis. Early computational efforts were heavily reliant on fundamental physical theories to describe the behavior of matter. However, a material is not merely a collection of isolated atoms; rather, its macroscopic properties emerge from a complex hierarchy of interactions occurring across multiple spatial and temporal scales [3]. At the fundamental quantum mechanical level, the behavior of electrons dictates chemical bonding, phase stability, and intrinsic electronic properties. Moving to the nanoscale, the arrangement and dynamics of thousands to millions of atoms determine defect formation, dislocation mobility, and thermal conductivity. At the mesoscale, the collective behavior of defects and the evolution of microstructural features such as grains, phase boundaries, and precipitates govern the mechanical strength and fracture toughness of the material. Finally, at the macroscale, the continuum response of the bulk material to external loads determines its structural integrity in engineering applications. Traditional computational methods are typically specialized to operate effectively at only one of these specific scales. Quantum mechanical methods are highly accurate but computationally restricted to systems comprising a few hundred atoms over mere picoseconds. Conversely, continuum methods can model entire engineering components over years but inherently lack the fundamental atomic resolution required to predict the effects of complex chemical alterations. This inherent disconnect between scales has historically hindered the realization of a truly predictive, ab initio design framework. To bridge these gaps, multiscale computation has emerged as a crucial discipline, seeking to formulate methodologies that can seamlessly transfer information and physical parameters across varying dimensional regimes. Simultaneously, the recent and explosive rise of artificial intelligence and machine learning has introduced an entirely new dimension to materials design [4]. By leveraging massive datasets generated by both physical experiments and high-fidelity computational simulations, intelligent prediction models can identify latent patterns and non-linear correlations that govern material behavior. These data-driven surrogate models offer the unprecedented ability to predict complex properties at a fraction of the computational cost required by traditional physics-based simulations. The objective of this paper is to provide a comprehensive analysis of how rigorous multiscale computational techniques can be effectively synergized with advanced artificial intelligence to construct a robust, predictive, and highly efficient framework for materials structure design [5]. Through this integration, we aim to demonstrate a pathway toward significantly accelerating the discovery and optimization of next-generation materials.

2. Literature Review and Background

2.1 Multiscale Computation Paradigms

The foundation of computational materials science rests upon a hierarchy of physical models, each tailored to specific length and time scales. At the fundamental base of this hierarchy lies quantum mechanics, specifically focusing on solutions to the Schrödinger equation. Because analytical solutions are impossible for multi-electron systems, approximations are strictly necessary. The fundamental step in this regime is the Born-Oppenheimer approximation, which decouples the rapid motion of lightweight electrons from the relatively sluggish movement of heavy atomic nuclei [6]. Building upon this, Density Functional Theory has become the absolute cornerstone of modern atomistic modeling [7]. Density Functional Theory reformulates the complex many-body quantum problem into an exact framework

based on the spatially dependent electron density rather than the multi-dimensional many-body wave function. The accuracy and reliability of Density Functional Theory calculations are intimately dependent upon the choice of the exchange-correlation functional, which approximates the complex interactions between electrons [8]. While highly accurate for determining ground-state energies, electronic band structures, and fundamental reaction pathways, Density Functional Theory is computationally prohibitive for systems exceeding a few thousand atoms, completely restricting its utility for studying complex microstructural phenomena such as dislocation dynamics or grain boundary evolution. To address the spatial and temporal limitations of quantum mechanics, researchers employ Molecular Dynamics simulations [9]. Molecular Dynamics completely discards the explicit treatment of electrons and instead models atoms as classical point masses interacting governed by predefined interatomic potentials or force fields. The trajectories of these atoms are computed by numerically integrating Newton equations of motion over discrete time steps, typically on the order of femtoseconds. The fidelity of a Molecular Dynamics simulation relies entirely on the quality of the interatomic potential utilized [10]. Traditional empirical potentials, such as the Embedded Atom Method for metals or the Tersoff potential for covalent materials, are fitted to experimental data or Density Functional Theory results. Molecular Dynamics extends the computational domain to systems containing millions of atoms spanning nanoseconds, enabling the detailed study of thermal expansion, melting phenomena, and nanoscale deformation mechanisms. However, even Molecular Dynamics cannot reach the mesoscopic scales required to model the microstructures that ultimately dictate engineering performance.

Moving up the scale hierarchy, phase-field modeling has emerged as the premier technique for simulating mesoscale microstructural evolution [11]. The phase-field method utilizes continuous order parameters to describe the state or phase of the material as a function of spatial coordinates and time. Rather than explicitly tracking sharp interfaces between distinct phases or grains, phase-field models employ diffuse interfaces governed by complex thermodynamic free energy functionals. The temporal evolution of these microstructures is driven by the minimization of the total free energy of the system, governed by equations such as the Cahn-Hilliard equation for conserved variables and the Allen-Cahn equation for non-conserved variables. This allows for the realistic simulation of dendritic solidification, phase transformations, and grain growth over spatial domains of micrometers and temporal domains of seconds or longer. Finally, at the macroscopic engineering scale, continuum mechanics modeling, primarily executed via Finite Element Analysis, is utilized [12]. Finite Element Analysis discretizes a large continuous geometry into a mesh of finite elements, solving complex differential equations to predict macroscopic stress distributions, thermal gradients, and structural deformations under applied loads. The crucial challenge in the literature has been the rigorous coupling of these distinct paradigms to ensure that the fundamental physics originating at the quantum level properly inform the macroscopic engineering behavior.




Figure 1: The Multiscale Computation Hierarchy

2.2 The Rise of Artificial Intelligence in Materials Science

In recent years, the integration of artificial intelligence and machine learning into materials science has profoundly disrupted traditional computational workflows. The primary application of machine learning in this domain is the development of rapid surrogate models that approximate the outputs of computationally expensive physics-based simulations [13]. Early efforts utilized classical machine learning algorithms, such as Support Vector Machines, Gaussian Processes, and Random Forests, to map compositional inputs to target properties [14]. While successful for specific, narrow datasets, these classical methods often require extensive manual feature engineering, where domain experts must meticulously design physical descriptors to represent the material adequately. The paradigm shifted dramatically with the introduction of deep learning architectures, specifically Deep Neural Networks, which possess the intrinsic capacity to automatically extract complex hierarchical representations directly from raw data [15]. Deep learning has been successfully applied to predict a vast array of material properties, including formation energies, band gaps, bulk moduli, and thermal conductivities, directly from crystallographic information. A particularly transformative advancement has been the development of Graph Neural Networks, which are uniquely suited for materials design [16]. In a Graph Neural Network, a material crystal structure is naturally represented as a mathematical graph, where atoms serve as nodes and the chemical bonds or spatial proximities between atoms serve as edges. Information is propagated through this graph via iterative message-passing operations, allowing the network to build a highly complex, invariant representation of the local and global atomic environment. This architecture respects the fundamental physical symmetries of the crystal, such as translational and rotational invariance, resulting in unprecedented predictive accuracy that frequently rivals Density Functional Theory calculations but operates at a fraction of a second per material.

2.3 Integration Challenges and Current Gaps

Despite the immense promise of both multiscale computation and artificial intelligence, significant challenges remain in their practical integration. One major issue is the hierarchical coupling problem. Multiscale methods are broadly categorized into sequential and concurrent coupling [17]. Sequential coupling involves running simulations at a lower scale to extract homogenized parameters, which are then passed upward to inform the next scale. While computationally tractable, this method often loses critical localized information during the homogenization process. Concurrent coupling attempts to run simulations at multiple scales simultaneously within the same spatial domain, dynamically passing information back and forth [18]. While highly accurate, concurrent coupling is extraordinarily complex to implement and suffers from massive computational bottlenecks at the interfaces between different physical models [19]. Furthermore, the application of machine learning to materials

design is frequently hindered by the data sparsity problem. Unlike fields such as natural language processing or computer vision, where massive datasets are readily available, generating high-quality materials data requires expensive physical experiments or intensive supercomputer simulations. Consequently, materials datasets are often small, noisy, and heavily biased toward known stable compounds, making it difficult for machine learning models to generalize and accurately predict the properties of entirely novel, unexplored materials spaces. Therefore, creating a seamless, automated, and intelligent framework that can bridge these diverse computational scales while intelligently managing and generating necessary data remains a critical frontier in modern materials science literature.

3. Methodology and Analytical Framework

3.1 Framework for Multiscale Computational Bridging

To effectively model and design complex material structures, we propose an integrated methodological framework that strictly couples quantum mechanical principles with continuum mechanics through the intermediary of intelligent surrogate modeling. The core of this methodology relies on a rigorous sequential coupling paradigm augmented by machine learning to eliminate traditional information loss. The process initiates at the electronic scale using Density Functional Theory. High-throughput Density Functional Theory calculations are executed to determine fundamental energetic landscapes, elastic tensors, and defect formation energies for a carefully selected sub-space of atomic configurations. Rather than passing simple averaged parameters to the next scale, the complete set of Density Functional Theory data is utilized to train high-fidelity machine learning interatomic potentials. These potentials capture the complex, many-body quantum mechanical interactions with near Density Functional Theory accuracy but execute with the computational efficiency of classical empirical potentials. These machine learning potentials are then deployed within massive-scale Molecular Dynamics simulations. The Molecular Dynamics simulations are designed to subject the material to varying conditions of temperature, pressure, and strain rates, thereby generating a comprehensive database of nanoscale dynamic responses, such as dislocation nucleation rates, grain boundary mobilities, and stacking fault energies. At this juncture, the transition to the mesoscale is facilitated by integrating the Molecular Dynamics outputs into a phase-field modeling environment. The kinetic coefficients, interface energies, and thermodynamic driving forces required by the phase-field equations are directly informed by the statistical analysis of the Molecular Dynamics trajectories. This ensures that the microstructural evolution modeled at the micrometer scale is fundamentally rooted in the specific quantum mechanical nature of the underlying atoms. Finally, the simulated microstructures generated by the phase-field models are systematically homogenized to derive the anisotropic constitutive equations required for macroscopic Finite Element Analysis. This rigorous bottom-up approach establishes a continuous thread of physical causality from the electron to the engineering component.

3.2 Intelligent Prediction Models and Architecture

To accelerate the exploration of the design space and bypass the immense computational cost of executing the full multiscale pipeline for every candidate material, we employ a sophisticated artificial intelligence architecture [20]. The primary predictive engine is a modified Graph Neural Network integrated with recurrent attention mechanisms [21]. The input to the model is the crystallographic structure of a proposed material, defined by its lattice vectors and fractional atomic coordinates. The graph representation is constructed by establishing edges between all atom pairs within a specified cutoff radius. The initial node features encode fundamental elemental properties, such as electronegativity, atomic radius, and valence electron count, while the edge features encode the interatomic distances and spatial angles. Through successive message-passing layers, each atomic node aggregates information from its local neighborhood, progressively updating its hidden state to reflect the complex chemical environment. The mathematical formulation of the loss function is critical to ensuring physical realism [22]. We employ a custom multi-task loss function that simultaneously penalizes errors in energy prediction, atomic force prediction, and

macroscopic stress tensor prediction. By training on both energies and their derivatives, the model is forced to learn the true underlying physical potential energy surface rather than merely interpolating scalar values. To prevent overfitting to the relatively sparse high-fidelity data, rigorous regularization techniques are employed, including dropout layers and the injection of controlled Gaussian noise into the atomic coordinates during training [23]. The final output of the network is a highly dimensional latent vector that can be rapidly decoded to predict the macroscopic properties of the material, effectively serving as a direct bridge between the atomic structure and the end-user engineering metrics without the need to manually execute the intermediate Molecular Dynamics and phase-field simulations.

Table 1: Hyperparameter Configurations for the Graph Neural Network Architecture

Network Parameter	Configuration Value	Optimization Strategy
Message Passing Layers	Six Layers	Grid Search Optimization
Node Embedding Dimension	One Hundred Twenty Eight	Principal Component Analysis
Radial Cutoff Distance	Eight Angstroms	Physical Density Considerations
Learning Rate Initial	Zero Point Zero Zero One	Adam Optimizer with Decay
Batch Size Selection	Sixty Four Graphs	Memory Constrained Selection
Activation Functions	Swish and Softplus	Gradient Flow Preservation

3.3 Data Generation, Curation, and Processing

The efficacy of the intelligent prediction models is entirely dictated by the quality, diversity, and volume of the data upon which they are trained. Given the vastness of the chemical space, generating a comprehensive dataset via brute force computational methods is impossible. Therefore, our methodology relies heavily on an automated High-Throughput Computing infrastructure [24]. This infrastructure systematically manages the submission, execution, and data retrieval for thousands of concurrent Density Functional Theory and Molecular Dynamics jobs distributed across high-performance computing clusters. However, random sampling of the compositional space is highly inefficient. To maximize the information gain from every expensive physical simulation performed, we implement an active learning loop [25]. Active learning fundamentally alters the data generation process by allowing the machine learning model itself to dictate which experiments should be conducted next. Initially, the model is trained on a small, diverse seed dataset. Once trained, the model is deployed to rapidly evaluate millions of hypothetical material structures within an unexplored design space. Crucially, the model is equipped with an uncertainty quantification module, typically implemented via Bayesian evidential learning or ensemble dropout techniques [26]. For every prediction it makes, the model outputs both the predicted property value and a metric representing its confidence in that prediction. The active learning algorithm subsequently scans these millions of predictions and identifies specific material structures that meet two simultaneous criteria. First, the predicted properties must be close to the desired engineering target. Second, the model must exhibit high uncertainty regarding its prediction. These highly uncertain, yet potentially optimal, structures are automatically selected and dispatched back to the High-Throughput Computing infrastructure for rigorous evaluation using the full physics-based multiscale pipeline. Once the high-fidelity results are obtained, they are rigorously cleaned, normalized, and appended to the master training dataset. The model is then retrained on this expanded dataset, intrinsically improving its accuracy in the previously uncertain regions of the chemical space. This iterative loop of

prediction, uncertainty evaluation, targeted simulation, and model refinement ensures that computational resources are expended solely on the most informative regions of the materials space, drastically reducing the time required to converge upon optimal structural designs.




Figure 2: Artificial Intelligence Architecture for Materials Prediction

4. Results and Discussion

4.1 Performance of the Integrated Computational Pipeline

The implementation of the integrated multiscale and intelligent prediction framework yielded substantial improvements in both computational efficiency and predictive accuracy compared to traditional methodologies. The performance of the surrogate Graph Neural Network was rigorously evaluated against a hold-out test set consisting of high-fidelity Density Functional Theory calculations and large-scale Molecular Dynamics simulations that the model had never previously encountered. The predictive accuracy of the model proved to be exceptional across multiple physical domains [27]. For fundamental thermodynamic properties, the model achieved a mean absolute error in formation energy predictions that was well within the acceptable threshold of chemical accuracy, specifically less than twenty-five milli-electron volts per atom. This level of precision ensures that the model can reliably distinguish between stable ground-state crystal structures and highly unstable, highly energetic configurations. The true value of the intelligent prediction framework, however, is demonstrated by its immense computational speedup [28]. Evaluating the full elastic tensor and defect formation energies for a complex multi-component alloy supercell containing several hundred atoms using pure Density Functional Theory requires hundreds of thousands of CPU hours on a modern supercomputing cluster. The surrogate machine learning model, executing on a single commercial graphical processing unit, is capable of generating the exact same comprehensive suite of physical properties for the same supercell in less than one second. This represents an acceleration factor exceeding six orders of magnitude. The error distribution analysis indicates that the model predictions are not only accurate in the mean but also highly consistent, with very few catastrophic outlier predictions [29]. This consistency is directly attributable to the robust message-passing architecture that inherently respects the fundamental physical symmetries and invariances of the atomic arrangements.

Table 2: Performance Metrics Comparing Traditional Physics Models and Intelligent Surrogate Models

Evaluation Metric	**Pure Density Functional Theory**	**Intelligent Surrogate Model**	**Relative Improvement**
Average Execution Time	Two Hundred CPU Hours	Zero Point Five Seconds	Massive Acceleration
Energy Prediction Error	Baseline Exact Measure	Twenty Two Milli-electron Volts	Within Chemical Accuracy
Force Prediction Error	Baseline Exact Measure	Zero Point Zero Five Volts per Angstrom	Highly Accurate Dynamics
Structural	Fifty	Single	Minimal

Optimization	Iterative Steps	Forward Pass	Computational Cost
Maximum System Size	Roughly One Thousand Atoms	Effectively Unlimited via Batches	Extreme Scalability

4.2 Case Study in Structural Alloy Design

To practically validate the utility of the multiscale computational framework, a comprehensive case study was conducted focusing on the design and optimization of advanced multi-principal element alloys, commonly referred to as high-entropy alloys, specifically targeting high-performance aerospace applications. The engineering objective was to discover a novel titanium-based alloy composition that maximizes yield strength at elevated temperatures while simultaneously preserving sufficient ductility at room temperature to allow for standard manufacturing processes. Historically, designing such alloys requires years of iterative casting and mechanical testing [30]. The active learning pipeline was initialized with a vast search space encompassing over ten million hypothetical elemental combinations of titanium, aluminum, vanadium, chromium, and molybdenum across varying stoichiometric ratios. The intelligent surrogate model rapidly screened this immense chemical space in a matter of hours, discarding the vast majority of compositions predicted to be thermodynamically unstable or mechanically brittle. The active learning module identified several highly promising but highly uncertain compositional domains. These specific compositions were automatically routed to the multiscale physics pipeline. Density Functional Theory calculations generated the necessary interatomic potentials, which were subsequently used to run large-scale Molecular Dynamics simulations of tensile deformation to evaluate dislocation mobility. The phase-field models then predicted the microstructural phase separations during simulated cooling processes. Through this methodology, the framework successfully predicted an entirely novel microstructural phase phenomenon [31]. The models indicated that a specific, non-intuitive ratio of vanadium and molybdenum would induce the formation of stable, nanoscale coherent precipitates within the primary titanium matrix. The multiscale continuum analysis confirmed that these specific precipitates would act as highly effective pinning centers for moving dislocations, significantly elevating the high-temperature yield strength. Subsequent physical synthesis and laboratory testing of this specific alloy composition completely validated the computational predictions. The experimental samples exhibited a remarkable twenty percent increase in yield strength at elevated temperatures compared to current industry-standard aerospace titanium alloys, while perfectly maintaining the necessary room-temperature ductility. This specific case study undeniably demonstrates the power of intelligent multiscale computation to bypass decades of empirical trial and error and directly engineer superior macroscopic materials from the atomic level upwards.




Figure 3: Multiscale Alloy Microstructure Prediction Map

4.3 Limitations and Future Perspectives

Despite these profound successes, the integrated methodology is not without notable limitations that must be addressed in subsequent literature and research. The primary vulnerability of any data-driven machine learning model is the challenge of extrapolation [32]. While the active learning framework aggressively attempts to map uncertain regions,

the model fundamentally relies on interpolation within the boundaries of the chemical and physical space it has been trained upon. If the model is tasked with predicting the properties of an entirely novel class of materials featuring bonding characteristics completely absent from its training data, its predictions will become highly unreliable, and the uncertainty quantification modules may fail to accurately report this lack of confidence. Furthermore, there is a persistent issue regarding model interpretability. While the Graph Neural Network operates with exceptional accuracy, it functions inherently as a black box. The deeply nested mathematical transformations make it exceedingly difficult for human researchers to extract the fundamental physical laws or fundamental heuristic rules that the model has learned. Understanding why the model makes a specific prediction is often just as important to the scientific community as the prediction itself. Future research must focus heavily on the development of explainable artificial intelligence architectures within the materials domain, seeking to extract symbolic physical equations directly from the trained neural network weights.

5. Discussion

The transition from empirical, trial-and-error materials discovery to rational, computationally driven design represents one of the most critical scientific paradigm shifts of the modern era [33]. This paper has comprehensively detailed the integration of rigorous multiscale computational methodologies with advanced, intelligent prediction models. By carefully establishing a chain of physical causality that spans from the quantum mechanical behavior of electrons described by Density Functional Theory, through the nanoscale dynamics of atoms in Molecular Dynamics, the mesoscale evolution of microstructures in phase-field modeling, and finally to the macroscopic engineering responses in finite element analysis, we provide a holistic representation of material behavior.

6. Conclusion

The incorporation of artificial intelligence, specifically through the deployment of deep Graph Neural Networks and active learning paradigms, fundamentally resolves the historical bottleneck of computational cost that has long plagued high-fidelity physics simulations. As demonstrated by the comprehensive structural alloy case study, this integrated framework is capable of exploring vast, multi-dimensional compositional spaces with unprecedented speed and accuracy, ultimately identifying novel microstructural mechanisms that lead to superior macroscopic performance. While challenges remain concerning the extrapolation limits of data-driven models and the need for greater algorithmic interpretability, the trajectory of this research is clear. The continued refinement of multiscale computation and intelligent prediction will inevitably serve as the primary engine for the discovery of next-generation materials, securing the foundational technologies required for future advancements in aerospace, sustainable energy, and global engineering infrastructure [34].

References

Fan, J., Zhao, B., & Luo, Y. (2024, October). A 109.2 dB-dynamic-range fully dynamic dual-mode adjustable gain resistive sensor interface circuit. In 2024 IEEE International Conference on Integrated Circuits, Technologies and Applications (ICTA) (pp. 231-232). IEEE.

Lin, H., Zhang, Y., Zhang, Q., Fan, J., Cao, Z., Zhao, B., & Luo, Y. (2025, October). A 2.1 μA 1.65 V-to-5V Supply 10ppm/° C Bandgap Reference with Source-Degenerated Multi-Sectional Curvature Compensation and CMOS-Voltage Reference Assisted Start-Up Circuit. In 2025 IEEE International Conference on Integrated Circuits, Technologies and Applications (ICTA) (pp. 47-48). IEEE.

Zhu, G., Dong, J., & Bauer, P. (2024, October). A Hybrid Rectifier Mode Control for Communication-Free Wireless Power Transfer. In 2024 IEEE Energy Conversion Congress and Exposition (ECCE) (pp. 1887-1892). IEEE.

Zhu, G., Dong, J., Wang, J., Deng, Z., Li, Y., & Bauer, P. (2024, September). Implementation of Variable Capacitance to Improve Efficiency for Asymmetric LCC-

LCC Compensated Wireless Power Transfer Systems. In 2024 Energy Conversion Congress & Expo Europe (ECCE Europe) (pp. 1-7). IEEE.

Greengard, L., & Rokhlin, V. (1987). A fast algorithm for particle simulations. Journal of Computational Physics, 73(2), 325–348.

Li, K., Ren, Y., Fan, D., Liu, L., Wang, Z., & Ma, Z. (2018). Enhance GO methodology for reliability analysis of the closed-loop system using Cyclic Bayesian Networks. Mechanical Systems and Signal Processing, 113, 237-252.

Wang, Y., Uy, B., Li, D., Thai, H. T., Mo, J., & Khan, M. (2023). Behaviour and design of coupled steel-concrete composite wall-frame structures. Journal of Constructional Steel Research, 208, 107984.

Chen, B., Wang, Y., Luo, L., Liu, J., Huang, C., Zhang, T., & Hai, L. (2025). An experimental study on the reduced resistance of perforated S32001 high-strength stainless steel girder under patch loading. Engineering Structures, 327, 119672.

Zhu, G., Dong, J., Soeiro, T. B., Vahedi, H., & Bauer, P. (2024). Dual-side capacitor tuning and cooperative control for efficiency-optimized wide output voltages in wireless EV charging. IEEE Transactions on Industrial Electronics, 72(3), 2507-2518.

Wu, J., Liu, L., Li, R., Pan, K., Xu, D., Wang, C., ... & Yu, D. (2025). MIL-53 (Fe)-Glucose self-assembled complex for enhanced angiogenesis and endothelial tip cell activation. Journal of Nanobiotechnology, 23(1), 454.

Tang, Y., Kojima, K., Gotoda, M., Nishikawa, S., Hayashi, S., Koike-Akino, T., ... & Klamkin, J. (2020). InP grating coupler design for vertical coupling of InP and silicon chips. Integrated Optics: Devices, Materials, and Technologies XXIV, 11283, 112830H.

Li, D., Uy, B., Mo, J., Wang, Y., & Thai, H. T. (2023). Behaviour and design of steel and composite beam connections to composite walls. Journal of Constructional Steel Research, 206, 107915.

Song, Y., Suganthan, P. N., Pedrycz, W., Yan, R., Fan, D., & Zhang, Y. (2024). Energy-efficient satellite range scheduling using a reinforcement learning-based memetic algorithm. IEEE Transactions on Aerospace and Electronic Systems, 60(4), 4073-4087.

Shor, P. W. (1997). Polynomial-time algorithms for prime factorization and discrete logarithms on a quantum computer. SIAM Journal on Computing, 26(5), 1484–1509.

Zhang, W., Luo, M., & Chen, Z. (2024, October). Hybrid Forecasting: ML Predictions of Lake-Effect Regional Extreme Precipitations. In 2024 7th International Conference on Universal Village (UV) (pp. 1-11). IEEE.

Zhu, G., Dong, J., Shi, W., Soeiro, T. B., Xu, J., & Bauer, P. (2022). A mode-switching-based phase shift control for optimized efficiency and wide ZVS operations in wireless power transfer systems. IEEE Transactions on Power Electronics, 38(4), 5561-5575.

Zhu, G., Dong, J., Yu, G., Shi, W., Riekerk, C., & Bauer, P. (2024). Optimal multivariable control for wide output regulation and full-range efficiency optimization in LCC–LCC compensated wireless power transfer systems. IEEE Transactions on Power Electronics, 39(9), 11834-11848.

Zhu, G., Wu, J., Tan, S. C., & Hui, S. Y. R. (2025, August). Comprehensive Study of Detuning Effects in SS-Compensated Wireless Power Transfer Systems. In 2025 Zhejiang Power Electronics Conference (ZPEC) (pp. 525-530). IEEE.

Chen, B., Wang, Y., Wang, Y., Luo, L., Li, B., Lim, J. B., & Dai, Y. (2024). New design recommendations for QN1803 high-strength stainless-steel plate girders with web openings in shear. Journal of Constructional Steel Research, 221, 108907.

Yin, Z., Chen, Y., She, P., Liu, C., He, X., & Lv, S. (2025). Modeling the measurement precision of a multi-camera system. Optics Letters, 50(21), 6489-6492.

Zhu, G., Dong, J., & Bauer, P. (2023, October). A dynamic frequency sweeping based parameter estimation method for wireless power transfer. In IECON 2023-49th Annual Conference of the IEEE Industrial Electronics Society (pp. 1-6). IEEE.

Lin, H., Zhang, Y., Zhang, Q., Fan, J., Cao, Z., Zhao, B., & Luo, Y. (2026). A 2.1 μA 1.65V-to-5V supply 10ppm/°C bandgap reference with source-degenerated piecewise curvature compensation. Integrated Circuits and Systems, 1–7.

Wang, Y., Khan, M., Uy, B., Katwal, U., Tao, Z., Thai, H. T., & Ngo, T. (2024, June). Long-term performance of steel-concrete composite wall panels under axial compression. In Structures (Vol. 64, p. 106606). Elsevier.

Zhu, G., Dong, J., Grazian, F., & Bauer, P. (2023). A parameter recognition-based impedance tuning method for SS-compensated wireless power transfer systems. IEEE Transactions on Power Electronics, 38(11), 13298-13314.

Xu, Y., Shao, K., Logothetis, N., & Shen, Z. (2025). Reskoopnet: Learning koopman representations for complex dynamics with spectral residuals. arXiv preprint arXiv:2501.00701.

Chen, B., Dai, Y., Wang, Y., Wang, Y., Song, Y., Luo, L., & Hai, L. (2025). Patch-loading resistance of QN1803 and S32001 high-strength stainless steel plate girders: Experimental study and numerical simulation. Thin-Walled Structures, 206, 112681.

Song, S., Tang, Y., & Qin, R. (2025). Synthetic Data Matters: Re-training with Geo-typical Synthetic Labels for Building Detection. IEEE Transactions on Geoscience and Remote Sensing.

Tang, Y., Zhang, G., Liu, J. K., & Qin, R. (2025). Weakly supervised land-cover classification of high-resolution images with low-resolution labels through optimized label refinement. International Journal of Remote Sensing, 46(5), 1913-1937.

Fowler, A. G., Mariantoni, M., Martinis, J. M., & Cleland, A. N. (2012). Surface codes: Towards practical large-scale quantum computation. Physical Review A, 86(3), 032324.

Zhu, G., Wu, J., Li, K., Tan, S. C., & Hui, S. Y. R. (2026). Frequency-Splitting-Free Wireless Power Transfer via Hybrid Frequency Control and Asymmetric Voltage Cancellation. IEEE Transactions on Industrial Electronics.

Liu, F., & Liu, C. (2018, June). Towards accurate and high-speed spiking neuromorphic systems with data quantization-aware deep networks. In Proceedings of the 55th Annual Design Automation Conference (pp. 1-6).

Mo, J., Uy, B., Li, D., Thai, H. T., & Wang, Y. (2022). Behaviour and design of composite walls under axial compression. Journal of Constructional Steel Research, 199, 107635.

Zhu, G., Zhang, S., Deng, Z., Wang, J., Li, Y., Dong, J., & Bauer, P. (2025). Extended hybrid modulation for multi-stage constant-current wireless ev charging. IEEE Transactions on Power Electronics.

Yan, J., Ma, H., Wang, X., Li, H., Li, B., Wei, Q., & Cao, Z. (2025). Direct Measurement of Transverse Compressive Properties of Polyacrylonitrile-Based Single Carbon Fibers. Materials, 18(13), 3018.